WhisperKOOL®
The Future of KOOL

SC PRO SERIES



Key Features

- UV-C Lighting System add-on
- Side or rear power connection options
- Ideal for small to mid-sized wine cellars
- Efficient, quiet cooling with centrifugal fans
- Condensate system evaporates up to 3 oz/hr
- E-coated coils enhance durability and performance
- Bottle probe for precise liquid temperature control
- Maintains 30°F differential (55°F cellar, ≤85°F intake)

Features

The SC Pro Series systems incorporate the latest and greatest features in wine cooling into their design, at an affordable price. Advanced blower fans replace axial fans, which accelerates the flow of cold air in your cellar at an even distribution. A condensate evaporator has been added to effectively manage condensate produced by the coil (up to 3 ounces of condensate per hour). The unit also utilizes smart refrigerant metering that efficiently manages the flow of refrigeration through the system to ensure optimal performance. In order to keep your cellar at 55°F, the condenser intake should not exceed 85°F. This makes interior installation ideal for SC Pro Series units. Our Extreme Series units are better suited for exterior installations.

Specifications

Model	2000	3000	4000	8000
Cellar Size	300 cu. ft.*	650 cu. ft.*	1000 cu. ft.*	2000 cu. ft.*
BTU/h (85°F condenser air intake temperature)	1453	2049	2253	4241
Dimensions	17.5”L x 14.25”W x 15.75”H			21.64”L x 14.25”W x 22.56”H
Refrigerant	R-134a/R-513a			
HP	1/8	1/6	1/6+	1/2
Voltage Rating	115V (20 amp dedicated circuit required); 230V (subject to availability)			
Weight (lbs)	65			104
Amps	3.2 (running amps)	3.7 (running amps)	4.7 (running amps)	10.9 (running amps)
Drain Line	1/2” ID clear plastic tubing			
Installation	Through-the-wall, partially ducted			
Thermostat	Advanced digital display, liquid-temperature-measuring bottle probe (retractable cable)			
Temp. Delta	Can maintain a 55°F cellar temperature with up to 85°F condenser air intake temperature			
Ducting Options	Exhaust air can be ducted using the optional ducting kit			
Warranty	2-year limited warranty & up to an additional (6) month grace period for install / 5-year limited warranty (compressor)			

*Suggested cubic footage rating assumes cellar is properly sealed and insulated with a minimum R19 insulation value. Materials such as glass, stone, concrete, etc., will negatively affect the insulation value. Each wine cellar is unique, and heat load calculations should always be performed prior to selecting a cooling unit. WhisperKOOL reserves the right to make changes to this document without prior notice at its sole discretion.